
TPL Automated Pile Biscuit Loader

for Biscuits and Crackers on Piles

Quick, Gentle, Intuitive





Fully Automated Biscuit on Pile Feeder

Less Maintenance - Higher Performance

Master Technologies sets a new standard to biscuit packaging with its new fully automated packaging line. Proven servo technology cares for reliable and soft pile counting-portioning and gentlest transfer into the wrapping machine's chain. Thus leading to an exceptional packaging performance up to 500 piles per minute with 50 loading cycles.

The TPL Pile Loader can be assembled up to 12 channels and in the special version, can be manufactured with 16 or more channels.

The base TPL has 4 servomotors for the portioning, loading the piles. As option, thanks to the "Stop & GO" feature, each individual channels can be stopped automatically incase of missing products and restart, as well automatically, when products are available.

Intuitive touchscreen operation allows easy to set and memorize various piles format count recipes. The modern construction allows easy cleaning together with excellent accessibility all over the system. Working conditions can be visually inspected at any time. Altogether significantly reducing maintenance efforts.



Easy Maintenance

Visual inspection of working conditions thanks to large transparent front and back safety guards

Dedicated and well designed compact construction for excellent accessibility and easy cleaning



Flexible Product Change

Easy operation through intuitive touch screen to memorize different recipes

Adjustable handles with number indicators for different products length and width



Higher Reliability

Gentle product handling by proven servo-motors technology Easy cleaning, easy format change, easy maintenance and safe operation increase the system availability High Speed Operation



Technical data

SpeedUp to 50 Cycles/minPiles height40 mm in Standard Version

Up to 500 piles/min (depends by product)

Up to 80mm in Special Version

Products size Length 35 .. 70 mm Power 3-phases, 380–400 V, 50/60 Hz

Width 35..70 mm
Height 3..10 mm
Air 6 bar

Special Version available for


Options

Stop & Go Device to prevent uncompleted piles Up to 12 channels in Standard Version Up to 25 channels in Special Version Transparent guards for visual inspection


bigger sizes

Biscuits Channeling Plates
Rotary or Penny Stacker Devices
Vibratory Channels
Accumulation Conveyors
High Speed Flow-pack wrapping machine

Top view



Front view



Related Products



Rotary Stacker

- Rotary Stacker with automatic drop of products on the below cross conveyor in case of full accumulation and wrappers stop
- Adjustable to different sizes of products



Tear Strip Applicator

(crosswise)

- Continuous Motion
 Transversal Easy Opening
 Applicator
- Integrated into the Flow-Pack Wrapping Machine
- Up to 600 applications/min

www.mastertechnologies.eu

For more information

Master Technologies s.r.l. Via Goretta 92/b - Frazione Mappano 10072 Caselle Torinese - (Torino) - Italy Telephone +39 011 207 1811 Facsimile +39 011 207 4302

Subject to technical changes. © 10/2018 Master Technologies s.r.l. Printed in Italy.